



[www.euroncap.com](http://www.euroncap.com)

**EUROPEAN NEW CAR ASSESSMENT PROGRAMME  
(Euro NCAP)**

**SEAT BELT REMINDER ASSESSMENT PROTOCOL**

Version 1.0b  
June 2004

# Seat Belt Reminder Assessment Protocol

## 1. Introduction

It is well recognised that the correct wearing of seat belts is the most effective way of providing protection for vehicle occupants in a crash. Currently, wearing rates vary greatly across the European Union and research has shown that many of the non-wearers would use their seat belt with some encouragement. A small proportion of non-wearers will not be persuaded to use their belts.

Seat Belt Reminder (SBR) systems are intended to encourage the first of these groups to use their seat belt, whilst at the same time not be so annoying that the second group would take undesirable action to disable the system. Such action could include, tampering with or cutting electrical connections which might have undesirable consequences.

It is intended that habitual users who always put their seat belt on, before starting their journey, would hardly notice the existence of the system and would not be annoyed by it.

To avoid the danger that dedicated non-users would try to tamper with the system, it should be possible for it to be deactivated. Long term deactivation would cover this requirement. The system could also incorporate short term deactivation for individual journeys.

Although, simple seat belt reminder systems have been available for some time, the technology behind the more sophisticated systems is new. Euro NCAP has set some minimum requirements but wishes to allow the development of increasingly improved systems.

Some recommendations are made for how improvements may occur and these may eventually become Euro NCAP requirements. The expectation is that the requirements will develop in the light of further knowledge.

## 2. Information required from manufacturers

Before the SBR can be evaluated by Euro NCAP, it is necessary for the manufacturer to explain which seating positions are covered by the system and how the system is intended to work. Only those seating positions, requested by the manufacturer, will be assessed by Euro NCAP, even if the system extends to other seats.

## 3. Seat Occupancy Requirement

In the case of the driver's seat, occupancy can be assumed so the system does not have to be capable of detecting whether or not the seat is in use.

For the front seat passengers, seat use must be detected. Euro NCAP defines occupancy as use by an occupant larger, taller or heavier than a small female (5<sup>th</sup> percentile).

Rear seat occupant detection is not required but it is recommended.

#### **4. Seat Belt Use**

For all seats offered for assessment, seat belt use must be monitored. Their use needs to be identified at the start of the journey and any change of use must be detected throughout period of use of the vehicle.

#### **5. Removable Seats**

Where seats, covered by the reminder system, are removable as part of the car's normal usage, Euro NCAP has minimum standards for any electrical connections used by the reminder system.

It is recommended that such electrical connections are made automatically when the seat is installed in the vehicle.

Alternatively, a manual connection can be made by the installer, provided that the following requirements are complied with:

- Connectors must be conspicuous and easily visible to the installer, during the installation process.
- Clear markings must indicate the purpose of the connection and show how the connection is made.
- The markings must be permanently attached to the vehicle.
- The markings must be conspicuous using contrasting colours.
- The markings must be easily visible to the installer during the installation process.

The presence or absence of the seat must not adversely affect the operation of other parts of the reminder system.

When the electrical connections are disconnected, the reminder system must operate normally as though the seat belt was not in use.

If the removable seat is optional, the assessment will be based on a car equipped with the optional removable seat.

#### **6. Start and Duration of Signal**

The reminder system should “start” at the commencement of each “journey” that the vehicle makes. Short breaks in the journey are allowed, where the reminder system is not required to start again. Such short breaks are to allow for events such as stalling of the engine or re-fuelling, where passengers may remain in the vehicle, etc.

## 6.1. Front seating positions

### Initial Signal

It is recommended that an audio and/or visual signal is started, shortly after the ignition is switched on or shortly after the vehicle starts to move, where one or more seat belts are not in use.

### Intermediate Signal

Optionally an intermediate signal may be given, at some time before the “Final Signal” is required, where one or more seat belts are not in use.

If this “Intermediate Signal” is more sophisticated than a simple audiovisual signal, the start of the Final Signal may be delayed. Such an Intermediate Signal might be a clear, easily visible text message or a loud and clear voice message.

### Final Signal

The audiovisual Final Signal is the only signal which is a Euro NCAP requirement, where one or more seat belts are not in use.

The start and duration requirements are defined as follows:

#### *Start*

The Final Signal must start before at least one of the following:

- The engine has been running for 60 seconds, or
- The car has been in “Forward Motion” for 60 seconds, or
- The car has been in Forward motion for 500 metres, or
- The car has reached a forward speed of 25 km/h

The choice of which one or more of the above criteria is used is optional.

Where a “more sophisticated Intermediate Signal” is employed, the start of the Final Signal may be delayed. However, the Final Signal must start before at least one of the following:

- The engine has been running for 90 seconds, or
- The car has been in “Forward Motion” for 90 seconds, or
- The car has been in Forward motion for 1000 metres, or
- The car has reached a forward speed of 40 km/h

The choice of which one or more of the above criteria is used is optional.

For the purpose of defining the start of the Final Signal, rearward motion or forward motion at less than 10 km/h is not deemed to be motion.

#### *Duration*

The duration of the Final Signal must be at least 90 seconds.

If the audiovisual Final Signal is not continuous:

- Gaps of more than 1 second in the signal must not occur more frequently than every 5 seconds.
- Gaps of less than 1 second, which allow for visual signals which flash and audio signals which “beep,” are ignored.
- If gaps in the signal exceed 3 seconds, that time is not included in the “Duration” time.
- No gap must last for more than 25 seconds.

Once the Final Signal has started, it must only stop under one of the following circumstances:

- The signal has operated for the Duration specified
- The related seat belts are put into use
- The ignition has been switched off
- The engine has been switched off

## 6.2. Rear seating positions

In the absence of seat occupancy information, only a visual signal is required by Euro NCAP. An audiovisual signal is recommended where seat occupancy information is available.

The start and duration requirements of the visual signal are defined as follows:

### *Start*

The signal must start within five seconds of at least one of the following:

- Engine start, or
- The start of forward motion

The choice of which one or more of the above criteria is used is optional.

For the purpose of defining the start of the signal, rearward motion or forward motion at less than 10 km/h is not deemed to be motion.

### *Duration*

The duration of the signal must be at least 30 seconds.

If the visual signal is not continuous:

- Gaps of more than 1 second in the signal must not occur more frequently than every 5 seconds.
- Gaps of less than 1 second, which allow for visual signals which flash are ignored.
- If gaps in the signal exceed 3 seconds, that time is not included in the “Duration” time.
- No gap must last for more than 25 seconds.

If the visual signal is more sophisticated than a simple warning light, such as a clear, easily visible text message, the system may allow the driver to acknowledge it, so switching the signal off.

No visual signal is required, if the system is able to determine that there are no occupants in the rear seating positions.

## **7. Signal**

Euro NCAP only requires the provision of simple audiovisual or visual signals. However, manufacturers are recommended to use the best possible means of communicating the reminder message to the driver and all the passengers. The provision of a visual signal for the user of each seat, the use of a loud and clear voice message or the use of a prominent text message on a satellite navigation or other LCD screen is recommended.

The signal should not annoy users, to the extent that they may be tempted to tamper with the restraint or the vehicle's electrical system.

A progressive or stepped audible signal is recommended. However, there is no requirement regarding the volume of any audible signal other than the Final Signal.

If for any reason, multiple audible signals are being generated at the time that the reminder signal is operating, they must not interfere with each other, to the extent that the message is less clear.

### **7.1. Front seating positions**

The Final Signal used for the front seating positions must be both audio and visual.

The audible component of the Final Signal must be "Loud and Clear," for the driver and all relevant passengers.

*Note: If, in future, an effective objective method of assessing a Loud and Clear signal is developed, Euro NCAP will consider its use for marginal cases.*

The visual signal and its message must be clearly visible to driver, without the need for the head to be moved from the normal driving position.

If flashing or intermittent visual or audible signals are used, they must be in synchronisation.

*Note: This requirement will be applied to any assessments first published after 1<sup>st</sup> January 2006.*

It is recommended that all front seat passengers can see the visual signal relevant to their seating position

It is recommended that the relevant visual signals are illuminated for the whole of the time that the seat is occupied without the seat belt being used.

### **7.2. Rear seating positions**

The signals for the rear seating positions need only be visual.

The visual signals and their message must be clearly and easily visible to driver, without the need for the head to be moved from the normal driving position.

It is recommended that all rear seat passengers can see the visual signal relevant to their seating position.

It is recommended that the relevant visual signals are illuminated for the whole of the time that the seat is occupied without the seat belt being used.

The visual signals, available for the driver, should clearly indicate the number of seat belts in use or not in use.

## **8. Change of Status**

If, during the journey, any seat belt experiences a “change of status,” where a buckled belt is unbuckled, the reminder must indicate immediately or the reminder sequence must start, as if a new journey had commenced.

## **9. Test Conditions for Assessment of Loud and Clear Audible Signals**

- The sound level will be assessed by a user, having normal hearing acuity, sitting in the relevant seat.
- The assessment will be made with the vehicle being driven at constant speed, in second gear. Vehicles with automatic transmission will have it locked in second gear if this is possible.
- The ventilation fan will be set to its maximum setting.
- All ventilation vents will be fully opened, if this is possible.
- The radio / audio system will be switched off.  
*Note: It is recommended, that reminder systems are designed so that, if they sound whilst the radio / audio system is playing, they interrupt the radio / audio sound. Alternatively, the radio/ audio system could be used to convey the reminder message.*
- The air conditioning will be switched off, if this is possible
- With convertibles, the roof will be closed.
- All windows will be closed.

*Note: It is recommended that the reminder system is designed so that the audible signal can be easily heard under any normal usage conditions.*

## **10. Deactivation**

The reminder system may be designed to allow deactivation. Short term deactivation can cover a single journey. Long term deactivation may be used for dedicated non-users of seat belts. It is intended that this would reduce the likelihood that users might tamper with the system.

The Seat Belt Reminder system must not be deactivated at the time that the car is offered for sale.

### 10.1. Short term single journey deactivation

Short term deactivation must be more difficult than putting the seat belt on and off once.

*Note: This requirement will be applied to any assessments first published after 1<sup>st</sup> January 2006. Until then, belting and un-belting within 10 seconds will continue to be the minimum requirement.*

The Reminder system must reactivate if ignition is switched off for more than 60 seconds.

### 10.2. Long Term

Long term deactivation must require a sequence of operations, which could not be guessed at or carried out accidentally.

Re-activation must be simple.

Instructions for long term deactivation must not be supplied with car. However, they can be supplied to the user on their request.

Included with the deactivation instructions must be the instructions on how to reactivate the system.

If deactivation has to be carried out by dealer, reactivation may also be carried out by the dealer.

In the case of low volume, special purpose vehicles, the Euro NCAP Secretariat can give ad hoc approval for the non-fitting of the SBR system to those vehicles.

## 11. **Scoring**

For Seat Belt Reminder systems which fully comply with the Euro NCAP requirements, the following points will be awarded to the overall occupant score for that vehicle:

#### *Driver*

Driver's seating position 1 point

#### *Front Passenger Seats*

All front passenger seating positions 1 point

#### *Single Row Rear Passenger Seats*

All rear passenger seating positions 1 point

#### *Multiple Row Rear Passenger Seats*

For each of "n" rear passenger seats 1/n point

If the third or more row of seats is optional, on any variant, the assessment will be based on a vehicle fitted with the optional seats.

In future, up to two additional points may become available to reward very sophisticated systems with enhanced capability. Such capability is not yet defined.



## **12. Future Developments**

It is expected that the protocol will continue to develop, in the light of experience with these new systems. Consideration will also be given to converting some of the current recommendations to requirements.